L4 requirements changes to provide Production Subsetting capability.

These changes are based on the RTM baseline of 9/16/96; and was re-verified against the baseline of 09/16/96

Text explaining PGS RbR Requirement changes related to SDPS RbR changes - Several PGS RbR requirements and two L4s which help cover them are being included in this CCR to formalize a concept implicitly related to the production subsetting requirements, namely the DPS ability to insert data into a remote data server and to be able to acquire data from a remote data server. This capability is only required to support the AM-1 mission.

Changes since first submittal:

- 1. New L4s supporting the new SDPS Production Oriented Subsetting RbRs now include the conditional phrase "In support of reducing production data dependency flow bandwidth consumption during inter-DAAC network transmission," to make sure that these subsetting capabilities aren't assumed for all products and activities its only for those products which will become inter-DAAC traffic.
- 2. Except for PGS-0270#B, all of the DPS remote staging/destaging L4 requirements were being linked to the opposite staging/destaging RbR. These links have all been reversed.

Table 1: Reference table for RbRs and L4s linkage

RBR id	text	interpretatio	clar. tex	IA id	req	rel	text
TtBTt_IG		n text	t	2.10	key	101	
<u>SDPS0200#</u> <u>B</u>	In support of reducing production data dependency flow bandwidth consumption during inter-DAAC network transmission, the ECS shall support subsetting through the use of geographical masking (land/sea mask, snow/ice mask) for standard production as well as reprocessing.			S- DSS- 02905	new	<u>B</u>	In support of reducing production data dependency flow bandwidth consumption during inter-DAAC network transmission, the SDSRV CI shall provide the capability to subset data within a granule through the use of geographical masking (land/sea mask, snow/ice mask) for products specified in Appendix F - Data Type Matrix, of the current version of 304-
SDPS0210# B	In support of reducing production data dependency flow bandwidth consumption during inter-DAAC network transmission, the ECS shall support the application of lossless compression and decompression techniques on data set files for removal of data set fill pixels, for standard production as well as reprocessing.			<u>S-</u> <u>DSS-</u> <u>02906</u>	new	<u>B</u>	dependency flow bandwidth consumption during inter-DAAC network transmission, the SDSRV CI shall provide the capability to compress data set files losslessly by eliminating repeated fill pixel values.
<u>SDPS0210#</u> <u>B</u>	production as wen as reprocessing.			<u>S-</u> <u>DSS-</u>	<u>new</u>	<u>B</u>	In support of reducing production data dependency flow bandwidth consumption

02907

CCR # 96-1126A Page 3 of 9

					-
					during inter-DAAC network transmission, the
					SDSRV CI shall provide the capability to
					decompress losslessly on data set files.
SDPS0210#		<u>S-</u>	new	<u>B</u>	The PRONG CI shall be capable of
<u>B</u>		DPS-			compressing data being destaged to a SDSRV
		26000			CI at a remote DAAC.
SDPS0210#		<u>S-</u>	<u>new</u>	<u>B</u>	The PRONG CI shall be capable of
<u>B</u>		DPS-			decompressing data being staged from a
		26010			SDSRV CI at a remote DAAC.
SDPS0220#	In support of reducing production data	<u>S-</u>	<u>new</u>	<u>B</u>	In support of reducing production data
<u>B</u>	dependency flow bandwidth consumption during	DSS-			dependency flow bandwidth consumption
	inter-DAAC network transmission, the ECS shall	<u>02908</u>			during inter-DAAC network transmission, the
	support subsetting through swath width reduction				SDSRV CI shall provide the capability to subset
	by selection of a range of pixels from each swath				data within a granule by selecting data values for
	row, for standard production as well as				a specified range of contiguous pixels in each
	reprocessing.				swath scan line for products specified in
					Appendix F - Data Type Matrix, of the current
SDPS0230#	In support of reducing production data	<u>S-</u>	8792	В	The SDSR VCI shall provide the capability to
B	dependency flow bandwidth consumption during	DSS-	0,,,2	_	subset, subsample, or average data within a
<u></u>	inter-DAAC network transmission, the ECS shall	02902			granule based on Spectral band for products
	support subsetting by spectral band(s) selection,	02702			specified in Appendix F - Data Type Matrix, of
					the current version of 304-CD-005.
PGS-0190#B	for standard production as well as reprocessing. The PGS shall coordinate with the DADS on the	<u>S-</u>	new	В	The PRONG CI shall be capable of staging data
_	staging of data for product generation.	DPS-			from a SDSRV CI at a remote DAAC.
		<u>26030</u>			
PGS-0270#B	The PGS shall provide the capability to perform	<u>S-</u>	<u>new</u>	<u>B</u>	The PRONG CI shall be capable of destaging
	the following functions, at a minimum:	DPS-			data to a SDSRV CI at a remote DAAC.
	a. Allocate tasks among processors	<u>26020</u>			
	b. Suspend execution of tasks				
	c. Resume execution of a suspended task				
	d. Cancel execution of tasks				
	e. Request and verify the staging and/or destaging				
	of data stored in the DADS				
PGS-0270#B		<u>S-</u>	new	В	The PRONG CI shall be capable of staging data
		DPS-			from a SDSRV CI at a remote DAAC.
PGS-0440#B	The PGS shall accept from the DADS L0-L4 data	\$ 6030	<u>new</u>	<u>B</u>	The PRONG CI shall be capable of staging data
	products. Received information shall contain at a	DPS-			from a SDSRV CI at a remote DAAC.
		26020			

26030

CCR # 96-1126A Page 4 of 9

	<u> </u>					
	minimum: a. Product identification					
	b. L0-L4 data set					
	c. Metadata required for processing					
	d. Current date and time					
	e. DADS identification					
PGS-0450#B	The PGS shall accept from the DADS ancillary		<u>S-</u>	new	<u>B</u>	The PRONG CI shall be capable of staging data
	data sets. Received information shall contain at a		DPS-			from a SDSRV CI at a remote DAAC.
	minimum:		<u>26030</u>			
	a. Product identification					
	b. Ancillary data set					
	c. Metadata required for processing					
	d. Current date and time					
	e. DADS identification					
PGS-1240#B	The PGS shall send the generated Level 1 to		<u>S-</u>	<u>new</u>	<u>B</u>	The PRONG CI shall be capable of destaging
	Level 4 Standard Products to the DADS. These		DPS-			data to a SDSRV CI at a remote DAAC.
	products shall contain the following information		<u>26020</u>			
	at a minimum:					
	a. Product identification					
	b. L1-L4 data set					
	c. Product processing priority					
	d. Current date and time					
	e. Associated metadata			<u> </u>		
PGS-1250#B	The PGS shall send the DADS the calibrated	_	<u>S-</u>	new	<u>B</u>	The PRONG CI shall be capable of destaging
	ancillary data.		DPS-			data to a SDSRV CI at a remote DAAC.
			26020			

Table 2: Rqmts to be added to Level_4 class

L4 id	req_k ev	rel	req_type	req_status	ver_method	ver_status	CCR	clarification	text
<u>S-DSS-</u> 02905	new	<u>B</u>	functional	approved	<u>test</u>	unverified			In support of reducing production data dependency flow bandwidth consumption during inter-DAAC network transmission, the SDSRV CI shall provide the capability to subset data within a granule through the use of

CCR # 96-1126A Page 5 of 9

							geographical masking for products specified in Appendix F - Data Type Matrix, of the current
							<u>version of 304-CD-005.</u>
S-DSS-	new	В	functional	approved	test	unverified	In support of reducing production data
02906		_					dependency flow bandwidth consumption
02/00							during inter-DAAC network transmission, the
							SDSRV CI shall provide the capability to
							compress data set files losslessly by eliminating
							repeated fill pixel values.
S-DSS-	new	В	functional	approved	test	unverified	In support of reducing production data
02907		_					dependency flow bandwidth consumption
							during inter-DAAC network transmission, the
							SDSRV CI shall provide the capability to
							decompress losslessly on data set files.
S-DSS-	new	В	functional	approved	test	unverified	In support of reducing production data
02908		_				322.	dependency flow bandwidth consumption
02700							during inter-DAAC network transmission, the
							SDSRV CI shall provide the capability to
							subset data within a granule by selecting data
							values for a specified range of contiguous pixels
							in each swath scan line for products specified in
							Appendix F - Data Type Matrix, of the current
S-DPS-	new	<u>B</u>	functional	approved	test	unverified	The Profit of the capable of
26000							compressing data being destaged to a SDSRV
							CI at a remote DAAC.
S-DPS-	new	<u>B</u>	functional	approved	test	unverified	The PRONG CI shall be capable of
26010							decompressing data being staged from a
							SDSRV CI at a remote DAAC.
S-DPS-	new	<u>B</u>	<u>functional</u>	approved	<u>test</u>	unverified	The PRONG CI shall be capable of destaging
26020							data to a SDSRV CI at a remote DAAC.
S-DPS-	new	<u>B</u>	functional	approved	test	unverified	The PRONG CI shall be capable of staging data
26030							from a SDSRV CI at a remote DAAC

Table 3: RBR to Level_4 links to be added

I	RBR_id	L4 id
ſ	SDPS0200#B	<u>S-DSS-02905</u>
ſ	SDPS0210#B	<u>S-DSS-02906</u>

SDPS0210#B	S-DSS-02907
SDPS0210#B	S-DPS-26000
SDPS0210#B	<u>S-DPS-26010</u>
SDPS0220#B	S-DSS-02908
<u>SDPS0230#B</u>	<u>S-DSS-02902</u>
PGS-0190#B	<u>S-DPS-26030</u>
PGS-0270#B	<u>S-DPS-26020</u>
PGS-0270#B	S-DPS-26030
PGS-0440#B	S-DPS-26030
PGS-0450#B	S-DPS-26030
PGS-1240#B	S-DPS-26020
PGS-1250#B	S-DPS-26020

L4 id	req_ke	rel	text	Component_I	Req_K	Comp_Type	Dev_Category	Text
	y			d	ey			
<u>S-DSS-</u> <u>02905</u>	new	<u>B</u>	In support of reducing production data dependency flow bandwidth consumption during inter-DAAC network transmission, the SDSRV CI shall provide the capability to subset data within a granule through the use of geographical masking (land/sea mask, snow/ice mask) for products specified in Appendix F - Data	<u>DsGeECSDat</u> <u>aProduct</u>	461	Object	Develop	To provide a general interface for services provided by ECS Data Product objects. ECSDataProducts are the ESDTs that are science data objects generated by ECS.
			Type Matrix, of the current version of 304-CD-005.					
<u>S-DSS-</u> 02906	new	<u>B</u>	In support of reducing production data dependency flow bandwidth consumption during inter-DAAC network transmission, the SDSRV CI shall provide the capability to	<u>DsGeECSDat</u> <u>aProduct</u>	461	Object	Develop	To provide a general interface for services provided by ECS Data Product objects. ECSDataProducts are the ESDTs that are science data objects generated by ECS.

CCR # 96-1126A Page 7 of 9

S-DSS- 02907	new	<u>B</u>	compress data set files losslessly by eliminating repeated fill pixel values. In support of reducing production data dependency flow bandwidth consumption during inter-DAAC network transmission, the SDSRV CI shall provide the capability to decompress losslessly on data set files.	DsGeECSDat aProduct	461	Object	Develop	To provide a general interface for services provided by ECS Data Product objects. ECSDataProducts are the ESDTs that are science data objects generated by ECS.
S-DSS- 02908	new	<u>B</u>	The SDSRV CI shall provide the capability to subset data within a granule by selecting data values for a specified range of contiguous pixels in each swath scan line for products specified in Appendix F - Data Type Matrix, of the current version of 304-	DsGeECSDat aProduct	461	Object	Develop	To provide a general interface for services provided by ECS Data Product objects. ECSDataProducts are the ESDTs that are science data objects generated by ECS.
<u>S-DSS-</u> 02902	8792	В	rhe sps NV CI shall provide the capability to subset, subsample, or average data within a granule based on Spectral band for products specified in Appendix F - Data Type Matrix, of the	DsGeECSDat aProduct	461	Object	Develop	To provide a general interface for services provided by ECS Data Product objects. ECSDataProducts are the ESDTs that are science data objects generated by ECS.
<u>S-DPS-</u> <u>26000</u>	new	<u>B</u>	current version of 304 CD-005 The PRONG CI shall be capable of compressing data being destaged to a SDSRV CI at a remote DAAC.	DpPrDataMa nager	386	Object	Develop	This class defines attributes and operations for initializing and managing data granules required by a PGE during its execution. It also ensures data availability before the execution of a PGE. In case of input data is unavailable at our local system disk, it sends request to DataServer to stage data at a specific location that allocated by Resource Management. At the end of the successful execution

CCR # 96-1126A Page 8 of 9

								of a PGE, it asks DataServer to
								destage (archive) output data and asks
								Resource Management to deallocate
								the sources.
S-DPS-				DpPrCompre	New	Object	Develop	This Class is used to access the UNIX
26000				ssion			*	compress commands.
S-DPS-	new	<u>B</u>	The PRONG CI shall be capable	<u>DpPrDataMa</u>	386	Object	Develop	This class defines attributes and
26010			of decompressing data being	nager		-	-	operations for initializing and
			staged from a SDSRV CI at a	_				managing data granules required by a
			remote DAAC.					PGE during its execution. It also
								ensures data availability before the
								execution of a PGE. In case of input
								data is unavailable at our local system
								disk, it sends request to DataServer to
								stage data at a specific location that
								allocated by Resource Management.
								At the end of the successful execution
								of a PGE, it asks DataServer to
								destage (archive) output data and asks
								Resource Management to deallocate
								the sources.
S-DPS-				DpPrCompre	New	Object	Develop	This Class is used to access the UNIX
26010				ssion				compress commands.
S-DPS-	new	В	The PRONG CI shall be capable	DpPrDataMa	386	Object	Develop	This class defines attributes and
26020			of destaging data to a SDSRV CI	nager		3	•	operations for initializing and managing
			at a remote DAAC.					data granules required by a PGE
								during its execution. It also ensures
								data availability before the execution of
								a PGE. In case of input data is
								unavailable at our local system disk, it
								sends request to DataServer to
								stagedata at a specific location that
								allocated by Resource Management.
								At the endof the successful execution
								of a PGE, it asks DataServer to
	l			I				*
								destage (archive)output data and asks

CCR # 96-1126A Page 9 of 9

								the sources.
S-DPS-	new	<u>B</u>	The PRONG CI shall be capable	<u>DpPrDataMa</u>	386	Object	Develop	This class defines attributes and
<u>26030</u>			of staging data from a SDSRV	<u>nager</u>				operations for initializing and
			CI at a remote DAAC					managing data granules required by a
								PGE during its execution. It also
								ensures data availability before the
								execution of a PGE. In case of input
								data is unavailable at our local system
								disk, it sends request to DataServer to
								stage data at a specific location that
								allocated by Resource Management.
								At the end of the successful execution
								of a PGE, it asks DataServer to
								destage (archive) output data and asks
								Resource Management to deallocate
								the sources.

Table 5: New Component class entries

	Req_K Comp_Type		Dev_Category	Text		
Id	ey					
<u>DpPrCompre</u>	<u>New</u>	<u>Object</u>	<u>Develop</u>	This Class is used to access the UNIX		
ssion				compress commands.		

Table 6: New links from Level 4 to Component

Table 0. New links from Level_4 to Component	
L4 id	Component_Id
S-DSS-02905	<u>DsGeECSDataProduct</u>
S-DSS-02906	<u>DsGeECSDataProduct</u>
S-DSS-02907	<u>DsGeECSDataProduct</u>
S-DSS-02908	<u>DsGeECSDataProduct</u>
<u>S-DSS-02902</u>	<u>DsGeECSDataProduct</u>
S-DPS-26000	<u>DpPrDataManager</u>
S-DPS-26000	<u>DpPrCompression</u>
S-DPS-26010	<u>DpPrDataManager</u>
S-DPS-26010	<u>DpPrCompression</u>
<u>S-DPS-26020</u>	<u>DpPrDataManager</u>

CCR # 96-1126A Page 10 of 9

S-DPS-26030 DpPrDataManager